

5L4740013T000-00 - 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

Revision nr.3 Dated 06/12/2018 Printed on 25/03/2019 Page n. 1 / 9

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1	1	D	rn	А	 ct	id	Δ.	nti	fi	۵.	•
1		_	го	ш	 	101		111	ш	ш	П

Code: 5L4740013T000-00

Product name 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Powder coating for industrial application for the use of professional users only

1.3. Details of the supplier of the safety data sheet

Name EUROPOLVERI S.P.A.
Full address Via Galvani, 69
District and Country 36066 Sandrigo

strict and Country 36066 Sandrigo (VI)
ITALIA

Tel. +39 0444750643 Fax +39 0444750653

e-mail address of the competent person

responsible for the Safety Data Sheet info@europolveri.it

1.4. Emergency telephone number

For urgent inquiries refer to +39 0444750643

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: -

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.

Precautionary statements: --

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients



5L4740013T000-00 - 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

Revision nr.3 Dated 06/12/2018 Printed on 25/03/2019 Page n. 2 / 9

SECTION 3. Composition/information on ingredients/>>

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

Saturated Polyester Resin

CAS $58 \le x < 62$ Substance with a community workplace exposure limit.

EC INDEX

BARIUM SULFATE

CAS 7727-43-7 15 ≤ x < 16,5 Substance with a community workplace exposure limit.

EC 231-784-4

INDEX

Reg. no. 01-2119491274-35-XXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

Not specifically necessary. Observance of good industrial hygiene is recommended.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products. The product is combustible and, when the powder is released into the air in sufficient concentrations and in the presence of a source of ignition, it can create explosive mixtures with air. Fires may start or get worse by leakage of the solid product from the container, when it reaches high temperatures or through contact with sources of ignition.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use breathing equipment if fumes or powders are released into the air. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.



5L4740013T000-00 - 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

Revision nr.3 Dated 06/12/2018 Printed on 25/03/2019 Page n. 3 / 9

SECTION 6. Accidental release measures/>>

6.3. Methods and material for containment and cleaning up

Confine using earth or inert material. Collect as much material as possible and eliminate the rest using jets of water. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use.

7.2. Conditions for safe storage, including any incompatibilities

Keep the product in clearly labelled containers. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ESP España INSHT - Límites de exposición profesional para agentes guímicos en España	ESP Esr	paña INS	SHT - Límites	de exposición	profesional p	ara agentes d	uímicos en España 2	017
--	---------	----------	---------------	---------------	---------------	---------------	---------------------	-----

GBR United Kingdom EH40/2005 Workplace exposure limits

HRV Hrvatska NN13/09 - Ministarstvo gospodarstva, rada i poduzetništva

ITA Italia Decreto Legislativo 9 Aprile 2008, n.81

EU OEL EU Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC;

Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.

TLV-ACGIH ACGIH 2018

Saturated Polyester Resin										
Threshold Limit Value										
Type	Country	TWA/8h		STEL/15r	min					
		mg/m3	ppm	mg/m3	ppm					
OEL	EU	3				RESP				
OEL	EU	10				INHAL				
TLV-ACGIH		10				INHAL				
TLV-ACGIH		3				RESP				



5L4740013T000-00 - 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

Revision nr.3 Dated 06/12/2018 Printed on 25/03/2019 Page n. 4 / 9

SECTION 8. Exposure controls/personal protection/>>

				BARIUN	/ SULFATE				
hreshold Lim	it Value			27 (10)					
Туре	Country	TWA/8h		STEL/15	min				
,,	,	mg/m3	ppm	mg/m3	ppm				
VLA	ESP	10	• •	•	• •				
WEL	GBR	4							
GVI	HRV	4				RESP			
GVI	HRV	10				INHAL			
VLEP	ITA	0,5							
OEL	EU	0,5							
TLV-ACGIH		5							
redicted no-e	effect concent	ration - PNEC	;						
Normal value in fresh water						115	mg/l		
Normal valu	e for fresh water	er sediment					600,4	mg/kg	
Normal valu	e of STP micro	organisms					62,2	mg/l	
	e for the terres						207,7	mg/kg	
lealth - Derive	ed no-effect le	vel - DNEL / [DMEL						
	Eff	ects on consu	mers			Effects on	workers		
Route of exp	oosure Ac	ute Acu	te	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	loc	al syst	temic	local	systemic	local	systemic	local	systemic
Oral					13000 mg/kg bw/d				
Inhalation					10 mg/m3				10 mg/m3

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

During the risk assessment process, it is essential to take into consideration the ACGIH occupational exposure levels for inert particulate not otherwise classified (PNOC respirable fraction: 3 mg/m3; PNOC inhalable fraction: 10 mg/m3). For values above these limits, use a P type filter, whose class (1, 2 or 3) must be chosen according to the outcome of risk assessment.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

In the case of prolonged contact with the product, protect the hands with penetration-resistant work gloves (see standard EN 374).

Work glove material must be chosen according to the use process and the products that may form. Latex gloves may cause sensitivity reactions.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

Use a type P filtering facemask, whose class (1, 2 or 3) and effective need, must be defined according to the outcome of risk assessment (see standard EN 149).

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	powder	
Colour	blue	
Odour	odourless	
Odour threshold	Not available	
pH	Not available	
Melting point / freezing point	0 °C	
Initial boiling point	Not available	



5L4740013T000-00 - 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

Revision nr.3 Dated 06/12/2018 Printed on 25/03/2019 Page n. 5 / 9

SECTION 9. Physical and chemical properties .../>>

Boiling range Not available Flash point Not applicable **Evaporation Rate** Not available Flammability of solids and gases Not available Lower inflammability limit 20 g/mc Upper inflammability limit Not available Lower explosive limit 20 g/mc Upper explosive limit Not available Vapour pressure Not available Vapour density Not available

Relative density 1,52
Solubility IMMIXABLE WITH WATER

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

Explosive properties

Oxidising properties

Not available

Not available

Not available

Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The powders are potentially explosive when mixed with air.

10.4. Conditions to avoid

Avoid environmental dust build-up.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure



5L4740013T000-00 - 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

Revision nr.3 Dated 06/12/2018 Printed on 25/03/2019 Page n. 6 / 9

SECTION 11. Toxicological information .../>>

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

LD50 (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

BARIUM SULFATE LD50 (Oral) LD50 (Dermal)

> 5000 mg/kg Mouse

> 2000 mg/kg

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

BARIUM SULFATE

Solubility in water Degradability: information not available 0,1 - 100 mg/l

EPY 9.9.0 - SDS 1004.13



5L4740013T000-00 - 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

Revision nr.3 Dated 06/12/2018 Printed on 25/03/2019 Page n. 7 / 9

SECTION 12. Ecological information .../>>

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC:

None

ΕN



EUROPOLVERI S.P.A.

5L4740013T000-00 - 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

Revision nr.3 Dated 06/12/2018 Printed on 25/03/2019 Page n. 8 / 9

SECTION 15. Regulatory information/>>

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

None

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

EUH210 Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament



5L4740013T000-00 - 5L4740013T000 PURAL POLYESTER R4001 - QUALICOAT P-0414 LILAC SM M TS

Revision nr.3 Dated 06/12/2018 Printed on 25/03/2019 Page n. 9 / 9

SECTION 16. Other information .../>>

- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review: The following sections were modified: